


# MICROAXS MX-IIS101-W/MX-IIS101-B

7" Indoor Monitor for IP Intercom System



## Description

Microaxs intercom entry monitors are design-conscious products created as the ideal decorative accessory for your home. But there is more than style to consider. They actually offer an unparalleled level of technology, with functions and features designed to meet all requirements

## Features

- Support Hands-free video communication with door station, guard unit connected in the intercom system
- Support panel call to management
- Support max. 7-channel defense zone alarm
- Support monitoring to door stations and cameras connected
- Support remote unlock function by PC software
- Support elevator/lift control via gateway

## Video/Audio Function

- HD video monitoring with high performance CMOS
- 7-inch colored TFT LCD with resolution 1024 x 600
- Full capacitive touch screen
- Noise elimination and echo cancellation



## MX-IIS101

## 7" Indoor Monitor for IP Intercom System

### Technical Data

Model	MX-IIS101
System Parameters	
Processor	High-Performance Embedded SOC Processor
Operation system	Embedded Linux Operation System
Display Parameters	
Display screen	7-inch Colored TFT LCD
Display resolution	1024 x 600
Operation method	Capacitive Touch Screen, Touch Key
Operation interface	Delicate Flattened UI Operation Interface
Audio Parameters	
Audio input	Built-in Omnidirectional Microphone
Audio output	Built-in Loudspeaker
Audio compression standard	G.711 A
Audio compression rate	64 Kbps
Audio quality	Noise Elimination and Echo Cancellation
Network Parameters	
Ethernet	10/100 Mbps Self-Adaptive Ethernet
Network protocol	TCP/IP, UDP
Alarm Parameters	
Alarm input	7-channel Defense Zone Alarm Inputs
Device Interfaces	
Network interface	1 RJ-45 10/100 Mbps Self-Adaptive Ethernet Interface
RS-485	1 RS-485 Half-Duplex Port
I/O output	Unlock button
General	
Memory	100 Photos
Power supply	24V Power Over Ethernet - DC 24V
Power consumption	<10 W
Working temperature	-10° C to + 55° C (14° F to 131° F)



## MX-IIS101

## 7" Indoor Monitor for IP Intercom System

### Technical Data

Model	MX-IIS101
Working humidity	10% to 90%
Dimensions (L × W × H)	200 mm × 130 mm × 14.9 mm (7.9" × 5.1" × 0.6")
Certification	ROHS

### Appearance and Interfaces

