

MX-TOS-114

Audio Telephone for IP Intercom System



Description

Microaxs intercom entry monitors are design-conscious products created as the ideal decorative accessory for your home. But there is more than style to consider. They actually offer an unparalleled level of technology, with functions and features designed to meet all requirements

Features

- Support 24V non-standard power supply or additional DC24V power supply
- Support doorbell and SOS alarm function
- Support one apartment with more than one Indoor Station
- Support audio intercom between visitors and residents, residents and Guard Units
- Support audio intercom between any two apartments, but this product can only be called

Audio Function

- Can receive calls from the outdoor station and guard unit



MX-TOS-114

Audio Telephone for IP Intercom System

Technical Data

Model	MX-TOS-114
System Parameters	
Processor	High-Performance Embedded SOC Processor
Operation system	Embedded Linux Operation System
Audio Parameters	
Audio input	Built-in Omnidirectional Microphone
Audio output	Built-in Loudspeaker
Audio compression standard	G.711 A
Audio compression rate	64 Kbps
Audio quality	Noise Elimination and Echo Cancellation
Device Interfaces	
RS-485	No
I/O output	Unlock button
General	
Power supply	24V Power Over Ethernet, DC 24V
Power consumption	<10 W
Working temperature	-10° C to + 55° C (14° F to 131° F)
Working humidity	10% to 90%
Dimensions (L x W x H)	209.9x77.9x52.8mm
Certification	CE, ROHS




MX-TOS-114

Audio Telephone for IP Intercom System

Technical Data

Appearance and Interfaces



Index	Description
1	Speaker
2	Microphone
3	Volume Button
4	Unlock Button
5	Power Input 24V DC
6	RJ45 port for PoE Switch