

MX-DRF100

Microaxs 1 Way Dimming RF



Features

- Flush-mounted 1-way switching actuator 5A, KNX RF, Data Secure
- 2 Binary inputs for floating contacts such as buttons, switches, temperature sensor (I2)
- Optimised dimming output for Dimmable energy-saving lamps, LEDs, incandescent and halogen lamps, and Dimmable transformers.
- Easy to adapt to different lamps thanks to automatic load detection
- Adjustable dimming curve for precise and flicker-free dimming
- Secure communication via KNX-RF with support from KNX Data Secure
- Easy installation due to the compact housing
- Integrated temperature monitoring for increased operating safety, e.g. in the event of overload
- The binary inputs are assigned to the output as standard (function test before programming)

Specification

| | |
|-----------------------|---------------------|
| Model | MX-DRF100 |
| Operating voltage KNX | Bus voltage |
| Operating voltage | 230 V AC 50 – 60 Hz |
| Frequency | 50 – 60 Hz |



MX-DRF100

Microaxs 1 Way Dimming RF

Specification

| | |
|--------------------------------|-----------------|
| Model | MX-DRF100 |
| Installation type | Flush-mounted |
| Type of connection | Screw terminals |
| Number of channels | 1 |
| Type | Base module |
| Protection class | II |
| LED lamp (trailing edge) | 250 W |
| Incandescent/halogen lamp load | 250 W |

Diagram

