

MX-ESB-3SP

Electric Strike/Door Release

The MICROAXS MX-1224V-ES UniFLEX Electric Strike is Centerline Latch Entry strike designed for use with Cylindrical and Mortise locksets with up to ¾" (19mm) throw latchbolts. The quality construction makes the 45 series ideal for high traffic applications. The compact low profile design enables quick and easy installation where jamb space is limited.



Features

- Centerline Electric Strike.
- 4 Interchangeable Application Faceplates.
- Full Monitoring is Standard, Including: Latched and Unlatched Status, Keeper Closed and Deadlocked.
- Keeper Open Status Optional.
- Reversible Failsafe/Failsecure, no disassembly.
- 1/4" Horizontal Alignment Adjustment.
- Plated Architectural Finishes Available.
- For 5/8" latch or 3/4" latch with 1/8" door gap.
- Latch position status standard.
- Keeper closed & deadlocked/ unlocked status standard.
- Field selectable failsecure - failsafe.
- ¼" Horizontal alignment adjustment.
- Low profile, 1-3/16" deep & Plug-in wire connectors.
- Mounting tabs and Non-handed.
- All stainless steel parts with durable die cast body for corrosion resistance.
- Fewer moving parts for maximum life.
- Stainless steel standard with square corner faceplate.
- Aluminum standard with radius corner faceplate.



MX-ESB-3SP

Electric Strike/Door Release

Specification

Model	MX-ESB-3SP
Dual Voltage Coil	200/100mA @ 12/24V DC 140/70mA @ 12/24V AC
Latch Position Status (std)	SPDT, Dry 3Amp @ 30V
Keeper Closed & Deadlocked Status	SPDT, Dry 3Amp @ 30V
Keeper Open/Close Status (optional)	SPDT, Dry 3Amp @ 30V
Dimension	
MX-1224V-ES & MX-ESB-3SP-4R	1-1/4" W x 4-7/8" H x 1-3/16" D
MX-ESB-3SP-6R	1-1/4" W x 6-7/8" H x 1-3/16" D
MX-ESB-3SP-7R	1-7/16" W x 7-15/16" H x 1-3/16" D

Instruction

