

# MX-499EP-MP

## Explosion Proof Exit Switches

Specifically designed for applications where flammable vapors are cause for concern, like clean room, chemical plant, or refinery environments by eliminating the sparks or arc in the exit switch.

For use in hazardous and corrosive environments.

Class I, Zone 1, AEx de IIC T6...T4 Gb / Ex de IIC T6...T4 Gb X

Zone 21, AEx tb IIC T85°C...T135°C Db IP66 / Ex tb IIC T85°C...T135°C Db IP66 X

Class I, Division 2, Groups A, B, C, D

Class II, Division 2, Groups E, F, G

Class III UL50, 50E, 508, UL60079-0, -1, -7, -31 Type 3, 4, 4X, 12, 13



### Features

- Impact Resistant Non-Metallic Antistatic Material.
- No moving parts, virtually maintenance free.
- Corrosion Proof with F1 UV Protection.
- 1.5" Mushroom Button (Green or Red).
- Silicone Gasket on Enclosure and Actuator.
- Explosion Protected Contact Blocks.
- Clearance for 3/4" Bottom Feed NPT Fitting.
- Classified for Hazardous Locations.

### Application

- Chemical Plants.
- Refineries.
- Paint Shops.
- Cleaning Facilities.
- Loading Facilities for flammable gases.
- Hazardous Material Storage Facilities.

## MX-499EP-MP

## Explosion Proof Exit Switches

### Specification

Model	MX-499EP-MP
Dimensions	3.95 W x 4.21 H x 4.16" D
Contacts	1 N.O. and 1 N.C., momentary
IEC Rating	DC60V 5A DC-13
Operating Temperature	-50° C to 60° C

