

MX-ASE50

ANSI standard Push Switch

- MX-ASE50SS Exit Push Button (Stainless steel).
- MX-ASE50NL Exit Push Button (Night Luminous).
- Current Rating: 3A@36VDC Max.
- Mechanical Life: 1000000 tested.
- Suitable for Door: Hollow Door.
- Output Contact: NO\COM(NC\NO\COM is option).
- Dimensions:115*70*20(mm).



Overview

MX-ASE50 Push Switch is ANSI standard satin finish stainless steel access switch button, suitable for a variety of door frame, which is marketed after 500,000 successful test. It is with simple & ultra-narrow design, refined and elegant. The Push Switch is the Best Choice for Access Control Systems.

Features

- 1.Simple and elegant design.
- 2.Durable quality with imported stainless steel for faceplate and button.
- 3.Easy installation with NO/COM dry contact.
- 4.Long lifespan, 500000 Successful Test.
- 5.Available option for NO/NC/COM Output.
- 6.Door Release button with back box.
- 7.Suitable for hollow door frame and electrical box use.

MX-ASE50

ANSI standard Push Switch

Specification

Model	MX-ASE50SS	MX-ASE50NL
Material	SUS304 Stainless steel Panel, Steel Button	Night Luminous
Current Rating	3A@36VDC Max	
Output Contact	NO,COM Output	
Optional Functions	NO/NC/COM Output	
LED Night	Available option for Blue,Green or Red	
Mechanical Life	500000 Successful Test	
Suitable for Door	hollow door frame and electrical box use	
Operating temp	-10~+55°C(14-131F)	
Operating Humidity	0-95% (Non- condensing)	
Dimensions	115Lx70Wx20H (mm)	
Weight	0.2kg	

Related Images

