

MX-1206LSB

Electromagnetic Entry door lock

- With LED and signal output.
- Waterproof IP65 Can be customized.
- Holding Force: 600kg (1200Lbs).
- Current Draw: 12V/500mA 24V/250mA.
- LED indicates the door is unlock, Green indicates the door is lock.
- Suitable for: Wooden door , Glass door ,Metal door , Fireproof door.
- With Buzzer Can be customized.



Overview

MX-1206LSB, single door magnetic entry door lock, with the door status signal output and led indicate, specially used to normal glass door, wodden door, metal door, fire doors, and all kinds of door. Hoisting design, saves time and power when installation. Inward door, frameless glass door, narrow door all have a complete set of accessories. Special Anti-residual magnetic design makes automatic access control safer.

Features

1. With the door status signal output, passed 1200lbs super static linear tension tests.
2. Anti-residual magnetic design, keep constant tension.
3. Built-in reverse current protection device (MOV), performance stability , safety coefficient is higher.
4. Wear materials, durable.
5. Electromagnetic suction work completely, there is no mechanical failure.
6. Shell with high strength alloy material, anode hardening treatment.
7. Lock body with double insulation treatment.
8. Through the European CE and ROHS, MA certification in China.



MX-1206LSB

Electromagnetic Entry door lock

Specification

Model	MX-1206LSB
Holding Force	600kg (1200Lbs)
Lock Status Sensors	YES
Optional Functions	Relock Delay Timer,Buzzer
Rated Operating Voltage	12/24VDC
Surface finish for magnet	Zinc plated
Surface finish for armature plate	Zinc plated
Ambient temperature in °C	-10~+55°C (14-131F)
Suitable for	Wooden , Aluminum , Glass , Fireproof & Metal
Magnets Dimensions (L x W x D)	265Lx71Wx40H (mm)
Armature Plate Dimensions (L x W x D)	185Lx60Wx13H (mm)
Weight in kg	4.5kg
CE-mark for building	Yes
Rohs-mark for building	Yes
Current consumption	12V/600mA 24V/300mA
Lock Status Indicator	Double color LED, Red and Green

Related Images

