

MX-600LSWB

600Lbs Magnetic Door Lock

- Holding Force: 280kg (600Lbs).
- Lock Size: 250L*48W*25H (mm).
- Armature Plate: 180L*38W*11H mm).
- Current Draw: 12V/500mA 24V/250m.
- LED indicates the door is unlock, Green indicates the door is lock.
- No residual magnetism, no mechanical damage 90 degrees open for all kinds of doors with frame With Buzzer Customization Available.



Overview

MX-600LSWB wooden door, metal door, fire doors, small doors, the most widely used. Hoisting design, saves time and power when installation. Inward door, frameless glass door, narrow door all have a complete set of accessories. Special Anti-residual magnetic design makes automatic access control safer and more convenient.

Features

1. Wear materials, durable.
2. Lock body with double insulation treatment.
3. Anti-residual magnetic design, keep constant tension.
4. Built-in reverse current protection device (MOV), performance stability, safety coefficient is higher.
5. Electromagnetic suction work completely, there is no mechanical failure.
6. Shell with high strength alloy material, anode hardening treatment.
7. Through the European CE and ROHS, MA certification in China.
8. With LED (double color indicate), has door status signal output, passed 600lbs super static linear tension tests.



MX-600LSWB

600Lbs Magnetic Door Lock

Specification

Model	MX-600LSWB
Holding Force	280kg (600Lbs)
Lock Status Sensors	NO, NC, COM
Optional Functions	Relock Delay Timer, Buzzer
Rated Operating Voltage	12/24VDC
Surface finish for magnet	Zinc plated
Surface finish for armature plate	Zinc plated
Ambient temperature in °C	-10~+55°C (14-131F)
Suitable for	Wooden , Aluminum , Glass , Fireproof & Metal
Magnets Dimensions (L x W x D)	250Lx48Wx25H(mm)
Armature Plate Dimensions (L x W x D)	180L*38W*11H(mm)
Weight in kg	2.0kg
CE-mark for building	Yes
Rohs-mark for building	Yes
Current consumption	12V/500mA 24V/250mA

Related Images

