

MX-600LTDB

Small Magnetic Lock

- With signal output.
- Voltage: DC12V or DC24V.
- LED & Waterproof IP65 Customization Available.
- Holding Force: 260kg (600Lbs).
- Current Draw: 12V/500mA 24V/250mA.
- No residual magnetism, no mechanical damage
90 degrees open for all kinds of doors with frame.



Overview

MX-600LTDB, single door small magnetic lock, with the door state signal feedback, specially used to normal glass door, wooden door, metal door, fire doors, small doors. Hoisting design, saves time and power when installation. Inward door, frameless glass door, narrow door all have a complete set of accessories. Special Anti-residual magnetic design makes automatic access control safer and more convenient.

Features

1. With the door state signal feedback, passed 600lbs super static linear tension tests.
2. Anti-residual magnetic design, keep constant tension.
3. Built-in reverse current protection device (MOV), performance stability, safety coefficient is higher.
4. Wear materials, durable.
5. Electromagnetic suction work completely, there is no mechanical failure.
6. Shell with high strength alloy material, anode hardening treatment.
7. Lock body with double insulation treatment.
8. Through the European CE and ROHS, MA certification in China.



MX-600LTDB

Small Magnetic Lock

Specification

Model	MX-600LTDB
Holding Force	260kg (600lbs)
Lock Status Sensors	NO,NC,COM
Optional Functions	LED, Relock Delay Timer, Buzzer
Rated Operating Voltage	12/24VDC
Surface finish for magnet	Zinc plated
Surface finish for armature plate	Zinc plated
Ambient temperature in °C	-10~+55°C (14-131F)
Suitable for	Wooden , Aluminum , Glass , Fireproof & Metal
Magnets Dimensions (L x W x D)	250L*48W*25H (mm)
Armature Plate Dimensions (L x W x D)	180L*38W*11H (mm)
Weight in kg	2.2kg
CE-mark for building	Yes
Rohs-mark for building	Yes
Time Delay	0 /3 /6 /9 sec

Related Images

