

MX-800TDS

EM lock with Timer Dealy

- With delay and signal output.
- Voltage:DC12V or DC24V.
- Armature Plate:190L*45W*11H(mm).
- Current Draw: 12V/500mA 24V/250mA.
- LED indicates the door is unlock,Green indicates the door is lock.
- Time: 0/3/6/9sec.
- No residual magnetism, no mechanical damage 90 degrees open for all kinds of doors with frame.



Overview

MX-800TDS, single door waterproof magnetic lock, with the door status signal output, led indicates and time delay, specially used to normal glass door, wodden door, metal door, fire doors, and all kinds of door. Hoisting design, saves time and power when installation. Inward door, frameless glass door, narrow door all have a complete set of accessories. Special Anti-residual magnetic design makes automatic access control safer.

Features

- 1.With door status signal feedback and time delay, passed 800lbs super static linear tension tests.
- 2.Anti-residual magnetic design, keep constant tension.
- 3.Built-inreverse current protection device (MOV), performance stability ,safety coefficient is higher.
- 4.Wearmaterials, durable.
- 5.Electromagnetic suction work completely, there is no mechanical failure.
- 6.Shell with high strength alloy material, anode hardening treatment.
- 7.Lock body with double insulation treatment.
- 8.Through the European CE and ROHS, MA certification in China.



MX-800TDS

EM lock with Timer Dealy

Specification

Model	MX-800TDS
Holding Force	380kg (800Lbs)
Lock Status Sensors	YES
Optional Functions	Buzzer
Rated Operating Voltage	12/24VDC
Surface finish for magnet	Zinc plated
Surface finish for armature plate	Zinc plated
Ambient temperature in °C	-10~+55°C (14-131F)
Suitable for	Wooden , Aluminum , Glass , Fireproof & Metal
Magnets Dimensions (L x W x D)	285Lx55Wx29H (mm)
Armature Plate Dimensions (L x W x D)	190Lx45Wx11H (mm)
Weight in kg	2.6kg
CE-mark for building	Yes
Rohs-mark for building	Yes
Current consumption	12V/500mA 24V/250mA
Lock Status Indicator	Red and Green, double color LED
Relock Delay Timer	0,3,6,9 seconds open time delay is adjustable

Related Images

